



**BOSCH**

Invented for life

# NurseCall S37 Wristband Transmitter



- ▶ **Modern and attractive design**
- ▶ **Worn on the wrist or as a medallion**
- ▶ **Easy to use**
- ▶ **Waterproof**
- ▶ **Battery-level monitor**
- ▶ **Battery lifetime of 3 years**

Waterproof and lightweight, the S37 Wristband Transmitter enables the user to summon help at any time by pressing a button, which will activate a radio signal to a wireless NurseCall system. It may be worn comfortably as a wristwatch or as a medallion with an adjustable cord.

## Functions

By pressing the button of the S37 Wristband Transmitter, you can activate a call for help and the LED indicator of the transmitter will blink once.

The care personnel is immediately informed by the NurseCall system through the Main or Relay Unit and the connected devices.

In the meantime, the button and the LED indicator of the Main or Relay Unit will start blinking. An alarm/event data is displayed on the Main or Relay Unit and is stored in the buffer of the system.

Cancelling an alarm can be done in two ways. It is always possible on the Main or Relay Unit, or can be done locally by a magnet on the S37 Wristband Transmitter, available as an option.

The S37 Wristband Transmitter offers an IP67 waterproof protection and has a built-in automatic battery monitoring with battery low transmission. To ensure correct functioning, it will send an automatic radio daily message to the receiver through radio monitoring.

The call button is available in red or black.

In addition, signaling devices can be connected to the Main or Relay Unit: a red light placed over the room door, a corridor display, as well as pagers.

## Certifications and Approvals

CE

R&TTE 1999/5/EC

LVD 73/23/EEC

EMC 89/336/EEC

EN 50130-4

EN 300220-1

EN 60950-1

EN 55022

## Parts Included

Quant.	Component
1	S37 Wristband Transmitter

## Technical Specifications

Dimensions (H x W x D)	48 x 42 x 13.5 mm
Weight	22 g
Frequency	434.01 MHz
Protection class	IP 67 (EN 60529)
Power supply	3V lithium battery CR2025
Consumption	Transmission: < 20 mA Idle mode: < 3µA
Battery life	3 years, under the following conditions: 3 alarms transmissions without repetition per day and 1 daily test transmission (incl. battery status)
Battery alarm	at approx. 20 % remaining
Automatic battery test	daily check and at every alarm
Permissible temperature	0 °C to 55 °C
Stability (0 to +55 °C)	< 3 KHz
Modulation:	FSK
Antenna	Integrated loop
Radiated power	50 µW
Transmission time	2 x 1300 ms
Pause between transmissions	200 to 600 ms (random)
Minimum range in free field	250 m

## Ordering Information

<b>S37 Wristband Transmitter</b> with black button	<b>CRS-SB-423FI</b>
<b>S37 Wristband Transmitter</b> with black button and reset possibility	<b>CRS-SB-427FI</b>
<b>S37 Wristband Transmitter</b> with red button	<b>CRS-SB-433FI</b>
<b>S37 Wristband Transmitter</b> with red button and reset possibility	<b>CRS-SB-437FI</b>

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3453  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**